M3 Air-Cooled Mig Welding Torch


Ratings:

 $300 \text{A CO}_{2^1} 270 \text{A}$ mixed gas M21, EN60974-7 @ 60% duty cycle. 0.9mm-1.2mm wires

The Arc M3 is a true 300 Amp Torch which outperforms all Binzel $^{\circ}$ MB36 derivatives and is ideal for 1.2mm production work.

ARC M HIGH PERFORMANCE MIG TORCH PACKAGES

M3 Torches are supplied with a Euro termination as standard and are supplied 'ready to weld' with all wear parts fitted.



Wear Parts

Nozzles - 2 Piece

	Part Number	Description	Bore	Wall	Material
Α	AM3HDTN	Tapered Nozzle (Part 2)	12mm	3mm	Copper
	AM3HDCN	Conical Nozzle (Part 2)	14mm	3mm	Copper
	AM3HDCYN	Cylindrical Nozzle (Part 2)	19mm	3mm	Copper
Α	1•AM3HDNI	Nozzle Insulator(Part 1)			Copper

Nozzles - Single Piece

A2	AM3TN	Tapered Nozzle / Insulator Assy	12mm	2.25mm	Copper
	AM3CN	Conical Nozzle / Insulator Assy	14mm	2.25mm	Copper
	AM3CYN	Cylindrical Nozzle / Insulator Assy	19mm	2.25mm	Copper

B Contact Tips

		Size Wire Size		
Part Number	Description	(mm)	(mm-inch)	Material
Standard Series				
AM5CT09	Contact Tip	M8*29.5	0.9-0.035	CuCrZr
AM5CT10	Contact Tip	M8*29.5	1.0-0.040	CuCrZr
• AM5CT12	Contact Tip	M8*29.5	1.2-0.045	CuCrZr
A Series				
AM5CT10A	Contact Tip	M8*29.5	1.0-0.040	CuCrZr
AM5CT12A	Contact Tip	M8*29.5	1.2-0.045	CuCrZr
AM2CT10A	Contact Tip	M8*29.5	1.0-0.040	Copper
AM2CT12A	Contact Tip	M8*29.5	1.2-0.045	Copper

® All Trademarks are the property of their respective owners and usage is for cross reference only

C Tip Adaptors

Part Number	Description	Material
•AM3TAB	Tip Adaptor	Brass
AM3TAC	Tip Adaptor High Performance	CuCrZr

D Liners

Part Number	Description	Wire Size
•AM2524-30	Steel Liner x 3mt	1.0-1.2mm
•AM2524-40	Steel Liner x 4mt	1.0-1.2mm
•AM2524-50	Steel Liner x 5mt	1.0-1.2mm
AM1535-30	Steel Liner x 3mt	0.6-0.9mm
AM1535-40	Steel Liner x 4mt	0.6-0.9mm
AM1535-50	Steel Liner x 5mt	0.6-0.9mm

• Denotes torch package standard wear part set-up

SuperSoft -20 Premium Power Cables Perfect for extreme subzero working conditions





Miro Ciao